



329.00 EUR

incl. 19% VAT, plus [shipping](#)

- INTEL® Celeron-M Processor 1047UE + HM65 Chipset
- Support 1 \* DDR3 1066/1333MHz Single CH up to 8GB
- Support 1 \* Serial ATAIII (6Gb/s) Devices
- Support CFast card
- Support mSATA card (Share with Mini PCI-E)
- Support Mini PCI-E x 1
- 1 \* 24 bits Dual Channel LVDS header
- Support DVI-I Output
- Supports 2 \* Realtek RTL8111F-CG Gigabit LAN
- Support CPU Smart FAN

|                            |                                                                                                                                                                                  |
|----------------------------|----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| <b>Dimension (W*H*D)</b>   | 185 * 60 * 142 mm                                                                                                                                                                |
| <b>Construction</b>        | Aluminum housing                                                                                                                                                                 |
| <b>Colors</b>              | Black / HBJC381F39-1047-B                                                                                                                                                        |
| <b>MB model</b>            | JNF39-1047 (3.5 " SBC)                                                                                                                                                           |
| <b>CPU &amp; CHIP</b>      | INTEL® Celeron-M Processor 1047UE + HM65 Chipset                                                                                                                                 |
| <b>BIOS</b>                | AMI 32MB SMT Flash ROM                                                                                                                                                           |
| <b>Memory</b>              | 1 * SO-DIMM slot (DDR3-1333/1600Mhz_Max 8GB)                                                                                                                                     |
| <b>Storage Space</b>       | <ul style="list-style-type: none"> <li>1 * 2.5" SATA Device (Support SATA 6G / Max Height 9.5 mm)</li> <li>1 * m-SATA SSD Device (Mini PCI-E)</li> <li>1 * CFast card</li> </ul> |
| <b>Display Interface</b>   | <ul style="list-style-type: none"> <li>1 * DVI-I</li> <li>1 * LVD-24 bits ( Internal pin header)</li> </ul>                                                                      |
| <b>Network</b>             | <ul style="list-style-type: none"> <li>2 * RJ45 (RTL8111F-CG Gigabit LAN)</li> <li>WiFi (optional / JBC381F39W-1047-B)</li> </ul>                                                |
| <b>Audio</b>               | <ul style="list-style-type: none"> <li>2 * Line out</li> <li>1 * Mic in</li> </ul>                                                                                               |
| <b>Front I/O Port</b>      | <ul style="list-style-type: none"> <li>2 * USB 2.0</li> <li>2 * COM (Max 4 Ports)</li> </ul>                                                                                     |
| <b>Rear I/O Port</b>       | 4 * USB 2.0                                                                                                                                                                      |
| <b>Expansion Interface</b> | 1 * Mini PCI-E (Full-size)                                                                                                                                                       |
| <b>Power Source</b>        | <ul style="list-style-type: none"> <li>DC-12V Jack input</li> <li>Adapter : AC_90~240V / DC_12V_5A / 60W</li> </ul>                                                              |
| <b>Certification</b>       | <ul style="list-style-type: none"> <li>EMC : CE , FCC</li> <li>Safety : RoHS , ErP</li> </ul>                                                                                    |

|                      |                                                                                                                                                                                                                  |
|----------------------|------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| • <b>Environment</b> | <ul style="list-style-type: none"> <li>• Operating Temperature : 0 ~ 40■</li> <li>• Storage Temperature : 0 ~ 60■</li> <li>• Vibration During Operation : N/A</li> <li>• Shock During Operation : N/A</li> </ul> |
| • <b>Mounting</b>    | <ul style="list-style-type: none"> <li>• Wall mounting Kits</li> </ul>                                                                                                                                           |
| • <b>Packing</b>     | <ul style="list-style-type: none"> <li>• Net Weight■2.2KG</li> <li>• Gross Weight■3.5KG</li> <li>• Color Box Dimension■250(W) x 118 (D) x 295 (H) mm</li> </ul>                                                  |