



19.95 EUR  
incl. 19% VAT, plus [shipping](#)

<b>Based spec</b>	Interface	SATAIII
	Dimension	100*70*7.0 mm
	Weight	62~72 g
	Capacity	64GB-1TB
	SDram	128mb-1gb
	Flash type	Synchronous MLC NAND Flash
<b>Read/Write Performance</b>	Sequential Read	Up to 550MB/s
	Sequential Write	Up to 450MB/s
	4KB Sequential Read IOPS	74212
	4KB Sequential Write IOPS	68870
	4KB Random Read IOPS	74764
	4KB Random Write IOPS	1555
<b>Power Consumption</b>	Response Time	0.1ms
	Power Supply	5V±5%
	Standby	0.3W
<b>Reliability</b>	4KB Random Write	2W
	Write endurance: 8 years @ 100G write/day(32G)	
	Read endurance: unlimited	
	MTBF: >2,000,000 hours	
	Data retention: >20years @ 25°C	
	Data destroy do not support	
	Sudden power-off recovery support	
	S.M.A.R.T, NCQ, Trim and dynamic power management support	
	Static and dynamic wear-leveling	
	Bad block management algorithm	
ECC: Supports BCH ECC 16 / 24 / 40 bits in 1024 bytes		
<b>Environment</b>	Storage temperature: -55~95 °C	
	Operation temperature: 0-70°C	
	Humidity: 5%-95%	
	Vibration: 20G Peak, 10 ~ 2000Hz, (15mins/ Axis) x3 Axis	
Shock: 1500G (@0.5ms half sine wave)		