

429.00 EUR  
incl. 19% VAT, plus [shipping](#)

- Realtek LAN



- Intel® Apollo lake Processor (TDP 10W)
- Support 1 \* SO-DIMM DDR3L , up to 8GB memory
- 2 \* USB2.0, 4 \* USB3.0, 2 \* DP, 2 \* RJ45, 1 \* SD, 1 \* RS232 (RJ45 type)
- DC-12V\_60W FSP Adapter

|                 |   |
|-----------------|---|
| MB Model        | – JNF631-3350 / 3.5" SBC<br>– JNF631-4200 / 3.5" SBC  |
| Part No.        | – HBJC377F631-3550B (non-WIFI) / HBJC377F631W3550B (WIFI)<br>– HBJC377F631-4200B (non-WIFI) / HBJC377F631W4200B (WIFI)  |
| CPU/Chipset     | – Intel® Apollo lake Processor N Series (TDP 10W)   |
| Memory          | – 1 * SO-DIMM slots DDR3L-1600MHz , up to 8GB   |
| Storage         | – 1 * 2.5" SATA3 6Gb/s internal drive bay (Max Height 9.5 mm)<br>– 1 * M.2 SSD Device (M Key-2242)<br>– 1 * Micro SD card slot  |
| Network         | – 2 * Realtek GbE   |
| Expansion       | – 1 * full-size Mini-PCIe slot (for WiFi expansion)   |
| Rear Panel I/O  | – 4 * USB 3.0<br>– 2 * DP (Max. resolution:4096 x 2160@60Hz)<br>– 2 * RJ45<br>– 1 * DC-In jack<br>– 1 * RS232 (RJ45 type)<br>– 1 * Micro SD<br>– 1 * Audio (Line out + Mic) |
| Front Panel I/O | – 1 * Power button , 1 * Reset button<br>– 1 * Power LED , 1 * HDD LED<br>– 2 * USB 2.0 ports<br>– 1 * Line-out<br>– 2 * COM  |
| Power Source    | – FSP DC Adapter / AC 90~240V input / DC12V-5A-60W / LV6  |

|             |   |
|-------------|---|
| Compliance  | – CE, FCC, LVD, RoHS  |
| Safety      | – Vibration test: N.C<br>– Shock test: N.C  |
| Temperature | – Operating Temperature: 0 ~ 50° C<br>– Storage Temperature: -10 ~ 70° C                              |
| Dimensions  | – 185 (W) x 142 (D) x 48 (H) mm   |
| Packing     | – Net Weight: 1.4KG<br>– Gross Weight: 2.4KG<br>– Color Box dimension: 250 (W) * 118 (D) * 295 (H) mm |
| OS Support  | – Windows 7, Windows 8.1, Windows 10, Linux   |
| Warranty    | – 2 Year limited warranty   |